



# WMT900-TCP

## Wireless Modbus-TCP Transceiver

### APPLICATIONS:

- Building Automation
- HVAC Controls
- Remote Monitoring
- kW Metering
- Gas Metering
- Water/Flow Monitoring
- Emergency Generator Controls
- Lighting Controls
- Critical Asset Monitoring
- Access Control

### FEATURES:

- Plug-and-Play!
- Extended Ranges up to several miles
- 128 bit AES Encryption
- FIPS 197 Certified
- Great penetration ability
- Transparent to the network



The WMT900-TCP allows you to install a close or long range point-to-multipoint wireless Modbus TCP network at a fraction of the cost of installation labor, conduit and cable.

The WMT900-TCP features an easy to use, plug-and-play configuration, requiring no special programming tools or network management software.

Offering advanced security measures including 128 bit AES encryption and FIPS 197, makes the WMT900-TCP the solution for any facility.

AIC900-E SPECIFICATIONS	
Frequency	902-928 MHz (Direct Sequence Spread Spectrum - DSSS)
RF Transmission Rate	1.536 Mb/s
Data Throughput	935 Kb/s
Output Power	+21 dBm (4 Watts EIRP when used with 15 dBi antenna)
Receive Sensitivity	-97 dBm at 10e-4 BER (-112 dBm with 15 dBi antenna)
Radio Link Budget	148 dB with 15 dBi antenna
Range	40 Miles LOS with 15 dBi antenna
Radio Channels	12 non-overlapping
Connector Types	RPSMA, 2 Pin Power Plug , Ethernet RJ45 10/100BaseT
Power Consumption	Transmit: 2.4 W, Receive: 1.7 W (100ma @ 24VAC/DC)
Voltage	12-24 VAC/DC (isolated power supply required)
Temperature Range	-20° C to 70° C (-4° F to 158° F)
Dimensions	4.3" x 3.35" x 1.75" (109mm x 85 mm x 44.5mm)
Weight	Approximately .6 lbs
Certifications	FCC: R4N-AW900M IC: 5303A-AW900M
Communication Protocol	Modbus TCP



AIC Wireless  
 101 N. Washington Street  
 PO Box 5189  
 Sylvester, Georgia 31791  
 1-877-424-2953  
 229-776-2510  
 229-776-2512 (Fax)  
[sales@aic-wireless.com](mailto:sales@aic-wireless.com)

[www.aic-wireless.com](http://www.aic-wireless.com)